

Kiso™

de novo® WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 54" x Vertical 21"	

**Federal Specifications:** Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 20  
Passes NFPA 286 Corner Burn Test

- Performance Features:**
- Phthalate-free
  - No heavy metals or formaldehyde
  - Printed exclusively with water-based, low VOC inks
  - Microventing for permeability is available on a custom order basis
  - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
  - NSF/ANSI 342 certified for sustainability
  - CA Prop 65 compliant

**Permeability, Moisture and Mold:** Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from DeNovo wall can be used to help control un-wanted moisture inside a building envelope.

**INSTALLATION NOTE**

Kiso™ is a random match / reversible pattern  
For specifications and hanging instructions go to: [www.denovowall.com](http://www.denovowall.com)

de novo® WALL

Tel: 501-372-3550 Fax: 501-372-3553  
[www.denovowall.com](http://www.denovowall.com)

Copyright© 2018. All Rights Reserved  
Any copying or other use is expressly prohibited  
DeNovo Wall is a trademark.

MADE IN USA

